

Flight and Load test report - EN 12491:2001

Manufacturer Gin Gliders Inc.
Address 285-1 Galdam-Ri, Mohyun-Myun,
YongIn-City, Kyunggi-Do
449-855 Korea

Certification number: EP 038.2011
Type/model: Yeti Rescue #60
Total weight in flight: 220 kg

Description of tests	place:	date:	result:
1. Deployment system strength test A load of 700 N between each components	Villeneuve		OK
2. Speed of opening test - ref. A (2 times) Time from the instant of free drop until a load of 200 N is sustained Opening time Opening time	Villeneuve Villeneuve	19.01.2011 19.01.2011	< 5 seconds < 5 seconds
3. Descent rate and stability test - ref. A and B (2 times) The paraglider is released as the parachute begins to open, minimum 100 m descent. Stability 1 Sink rate 1 Stability 2 Sink rate 2	Villeneuve Villeneuve Villeneuve Villeneuve	19.01.2011 19.01.2011 19.01.2011 19.01.2011	Stable 5.21 m/s Stable 5.14 m/s
4. Strength test 40 m/s opening shock (2 times) The drop test device is accelerated to a straight line velocity of 40 m/s and the parachute deployment handle activated using a static line attached to a drogue chute. Speed of opening is less than 5 seconds Test 1 Test 2	Illarsaz Illarsaz	26.01.2011 26.01.2011	OK OK
5. Interaction and stability test (piloted) - ref. C a the emergency parachute is deployed from a paraglider in normal straight flight. b the pilot shall take no action while the behaviour of the parachute and paraglider are observed 200 metres. c the pilot take action while the behaviour of the parachute and paraglider are observed 200 metres.			not available not available not available

The model described is in conformity with the flight and load tests carried out by Air Turquoise SA.



For Air Turquoise SA


Alain Zoller

Air Turquoise SA
Route du Pré-au-Comte 8
Case postale 10
CH- 1844 Villeneuve
email: info@para-test.com

ISO 9001
BUREAU VERITAS
Certification



homepage: www.para-test.com

Weather data, ref. 3 and B

Date / place	hPa	wind	temp	humidity
19/01/2011 Villeneuve	972.5	0 km/h	0°	69.0%
	<i>Corrected mass:</i>	222.75		
19/01/2011 Villeneuve	972.5	0 km/h	1°	67.0%
	<i>Corrected mass:</i>	221.94		

Reference

A. At horizontal airspeed 8 m/s and vertical speed 1.5 m/s

B. Formula to be used for correcting the test mass ofr differences from ICAO standard atmosphere

$$m_{\text{corr}} := m_{\text{dec}} \cdot \frac{p \cdot T_0}{p_0 \cdot T}$$

Ground level atmospheric pressure at the test location: (p)

ICAO standard atmospheric pressure at MSL: (p₀)

Ground level température at the test location: (T)

ICAO standard temperature at MSL: (T₀)

Total weight in flight: (m_{dec})

Corrected mass: (m_{corr})

C. Only parachute with controls for steering and landing flare



Air Turquoise SA

Route du Pré-au-Comte 8

Case postale 10

CH - 1844 Villeneuve

Switzerland

mobile: +41 79 202 52 30

Tel. no : +41 21 965 65 65

fax : +41 219 65 65 68

email: info@para-test.com

homepage: www.para-test.com

For Air Turquoise SA

Alain Zoller

